

## TK1107 - PVA 2000 In-Line Dispenser (2004)

Model: 2000 In-Line Dispenser

SKU:

Year: 2004



### Description:

PVA 2000 In-line Dispensing/Coating System

Brand: PVA

Model: 2000

Type: Dispensing/Coating System, In-line

Year: 2004

Serial #: W2028

### Configuration:

Dispensing Valve 1

FCS100-ES (Extended Spray Valve)

Dispensing Valve 2

FC100 (Front Closing High-Pressure Valve, Micrometer)

Material Tank

5 gallon

Specifications:

Travel Speed

0 to 700 mm/sec (0 to 27.6 in/sec)

Payload Capacity

25 pounds (11.4 kg)

Standard Work Area

500 mm x 500 mm x 100 mm (19.68 in x 19.68 in x 3.94 in)

Repeatability

0.025 mm (0.0001 in)

Positional Resolution

0.005 mm (0.0002 in)

Power Requirements

120V, 220V, +/-10%, 50-60 Hz

Air Supply Requirements

80 PSI dry, unlubricated air

Conveyor Speed

Programmable up to 1.67 in/sec

Conveyor Compatibility

SMEMA

Conveyor Process Flow

Programmable right to left or left to right

Conveyor Edge Clearance

SMEMA standard 0.185 in

Belt Conveyor Weight Limit

5 pounds per section

Chain Conveyor Weight Limit

15 pounds per section

Certification

CE certified

